



ONLY
13
UNITS

**EXW
PRICE**

SAP45C-8S PAVER



SAP45C-8S
PAVER

Official Website:
www.sanyglobal.com

Contact: _____
E-mail: _____



Technical specifications

Model	SAP45C-8S (Code:TPJ100000162)
Paving Capacity (t/h)	320
Paving Width (m)	Hydraulic: 4.5
Basic Width (m)	Hydraulic: 1.7~3.1
Max. Paving Thickness (cm)	25
Working Speed (m/min)	1.5~20
Travel Speed (km/h)	0~2.2
Transport Size (mm)	Hydraulic: 6450 × 2100 × 3160
Engine Brand	DONGFENG CUMMINS
Engine Model	QSB4.5
Rated Power of Engine (kW)	97
Emission Standard	CHINA III
Voltage of Electric System (V)	24
Gradeability	≥ 20%
Hopper capacity (m ³)	6
Heating Mode	Electric Heated
Camber Adjustment Range (%)	-1~3
Tamps	1
Amplitude of Tamp (mm)	4
Frequency of Tamp (Hz)	0~25
Frequency of Oscillation (Hz)	0~25

技术参数

型号	SAP45C-8S (编码 :TPJ100000162)
最大理论生产能力 (t/h)	320
最大摊铺宽度 (m)	伸缩板: 4.5
基本宽度 (m)	伸缩板: 1.7~3.1
最大摊铺厚度 (cm)	25
工作速度 (m/min)	1.5~20
行驶速度 (km/h)	0~2.2
运输尺寸 (mm)	伸缩板: 6450 × 2100 × 3160
发动机品牌	东风康明斯
发动机型号	QSB4.5
额定功率 (kW)	97
排放标准	国 III
电控系统电压 (V)	24
最大爬坡能力	≥ 20%
料斗容量 (m ³)	6
加热方式	电加热
拱度调节范围 (%)	-1 ~ 3
振捣数量	1
振捣振幅 (mm)	4
振捣频率 (Hz)	0 ~ 25
振动频率 (Hz)	0~25

SANY HEAVY INDUSTRY CO., LTD.

SANY Industrial Park, Economic and Technological Development Zone, Changsha, Hunan, China, 410100
 Sales Hotline: Tel: 0086-731-85835199 Service Hotline: Tel: 0086-4006098318
 Mail: sales@sanyglobal.com Mail: CRD@sany.com.cn

The product configuration (including technical parameters) is subject to change and the delivered actual machine without notice.

www.sanyglobal.com