



SAP90C-8 PAVER



Powerful

- ◆ Wiring harnesses built to industry standards to provide solid connections and protection against heat, cold and moisture.
- ◆ The machine and its systems are designed to work non-stop, 24 hours a day under full load in a 50 degree Celsius environment.

Efficiency


- ◆ High strength screed – the strongest, most rigid design in the industry. Uses a frame structure with double layer anti-twist beams to produce consistently stable work.
- ◆ Anti-segregation technology used in all aspects of material handling. Fully proportional, independent conveyor and auger controls match device speeds to paving speed – fully and independently adjustable for various material types.
- ◆ To provide the ultimate in product support, machine controllers can be remotely monitored and even updated!

Technical specifications

Model	SAP90C-8
Paving capacity (t/h)	900
Paving width (m)	Hydraulic: 9.2
Basic width (m)	Hydraulic: 3~5.7
Max. paving thickness (cm)	35
Working speed (m/min)	1~16
Travel speed (km/h)	0~2.4
Transport size (mm)	7260 × 3110 × 3280
Engine brand	SANY
Engine model	D07S3-245E0
Rated power of engine (kW)	180
Emission standard	CHINA III
Voltage of electric system (V)	24
Gradeability	≥ 20%
Hopper capacity (m ³)	8.5
Heating mode	Electric heated
Camber adjustment range (%)	-1~3
Tamps	1
Amplitude of tamp (mm)	0/2/4/6/8
Frequency of tamp (Hz)	0~25
Frequency of oscillation (Hz)	0~50

Dimensions

Size code	SAP90C-8
A (mm)	3880
B (mm)	3280
C (mm)	3278
D (°)	15
E (°)	12.5
F (mm)	2600
G (mm)	2022
I (mm)	3660
L (mm)	7250



SANY HEAVY INDUSTRY CO., LTD.

SANY Industrial Park, Economic and Technological Development Zone, Changsha, Hunan, China, 410100
 Sales Hotline: 0086-731-85835199
 Mail: sales@sanyglobal.com

Service Hotline: 0086-4006098318
 Mail: CRD@sany.com.cn

The product configuration (including technical parameters) is subject to change and the delivered actual machine without notice.

www.sanyglobal.com